

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the above-identified application:

Listing of Claims

1. (Canceled)
2. (Canceled)
3. (Currently Amended) The seal of claim [[1]] 6, wherein the at least one first tooth is at an angle of between about 30 degrees and about 60 degrees relative to an outer surface of the first end and the at least one second tooth is at an angle of between about 30 degrees and about 60 degrees relative to the outer surface of the first end.
4. (Previously Presented) The seal of claim 3, wherein the at least one first tooth is at an angle of about 45 degrees and the at least one second tooth is at an angle of about 45 degrees.

5. (Canceled)

6. (Currently Amended) A seal usable between two thermally movable components, comprising:
a body for sealing space between adjacent components to prevent a fluid from passing through the space;

wherein the body has a cross-section that has a first side, a second side generally opposite to the first side, a first end, and a second end generally opposite to the first end, wherein the first and second sides have lengths longer than lengths of the first and second ends;

wherein the first end includes at least one first tooth extending from a region on the first end proximate to an intersection between the first end and the first side and extending toward the second side of the body and at least one second tooth extending from a region on the first end proximate to an intersection between the first end and the second side and extending toward the first side of the body;

~~The seal of claim 1,~~ wherein the at least one first tooth extending from the region on the first end proximate to the intersection between the first end and the first side comprise three teeth, and the at least one second tooth extending from the region on the first end proximate to the intersection between the first end and the second side comprise three teeth.

7. (Currently Amended) A seal usable between two thermally movable components, comprising:
a body for sealing space between adjacent components to prevent a fluid from passing through the space;
wherein the body has a cross-section that has a first side, a second side generally opposite to the first side, a first end, and a second end generally opposite to the first end, wherein the first and second sides have lengths longer than lengths of the first and second ends;
wherein the first end includes at least one first tooth extending from a region on the first end proximate to an intersection between the first end and the first side and extending toward the second side of the body and at least one second tooth extending from a region on the first end proximate to an intersection between the first end and the second side and extending toward the first side of the body;

~~The seal of claim 1, wherein the teeth are curved.~~

8-20. (Canceled)